

SAFETY DATA SHEET

Gulf Formula EFE, SAE 0W-20

01130/0W-20/1

Issuing Date: 05-16-2016

Revision Date: 05-16-2016

Version 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name	Gulf Formula EFE, SAE 0W-20
Product Code(s):	01130/0W-20/1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Engine oil

Uses advised against Any other purpose.

1.3. Details of the supplier of the safety data sheet

Supplier

Gulf Oil Supply Company Limited B2 Industry Street, Qormi, QRM 3000, Malta +44 207 321 6219 products@gulfoilltd.com sds@gulfoilltd.com

1.4. Emergency telephone number

Europe (+) 44 808 189 0979 Code 334276 (+) 1 760 476 3961 Code 334276 (+) 32 (0) 3241 33 55

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [GHS]

2.2. Label Elements

Signal Word None

Hazard Statements

EUH210 - Safety data sheet available on request

2.3. Other hazards

No information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances / 3.2. Mixtures

This product is a mixture. Health hazard information is based on its ingredients

Chemical Name	EC-No	CAS-No	Weight %	Classification (Reg. 1272/2008)	REACH Registration Number
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	-	-	50% - 100%	Asp. Tox. 1 (H304) (EUH066)	-
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	-	10% - 25%	**	-
Bis(nonylphenyl)amine	253-249-4	36878-20-3	1% - 2.5%	Aquatic Chronic 4 (H413)	01-2119488911-28-xxx x

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346 See Section 15 for additional information on base oils.

** Substances for which there are Community workplace exposure limits

Full text of H- and EUH-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice	If symptoms persist, call a physician.		
Inhalation	Move to fresh air.		
Skin contact	Wash off immediately with soap and plenty of water. Remove and wash contaminated clothing before re-use.		
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.		
Ingestion	Clean mouth with water. Drink plenty of water. Do not induce vomiting without medical advice.		
Protection of First-aiders	Use personal protective equipment.		
4.2. Most important symptoms and	effects, both acute and delayed		
Main Symptoms	None		
4.3. Indication of immediate medical attention and special treatment needed			
Notes to physician	Treat symptomatically.		

SECTION 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment:, Use CO2, dry chemical, or foam, Water spray or fog, Cool containers / tanks with water spray

Extinguishing media which shall not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire

5.2. Special hazards arising from the substance or mixture

Special Hazard

Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). In the event of fire and/or explosion do not breathe fumes. This material creates a fire hazard because it floats on water. Combustible material.

Hazardous Decomposition Products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Special protective equipment for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ensure adequate ventilation.

Advice for non-emergency Material can create slippery conditions.

Advice for emergency responders For personal protection see section 8.

6.2. Environmental precautions

personnel

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

6.3. Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dike to collect large liquid spills.

6.4. <u>Reference to other sections</u>

See Section 8/12/13 for additional information

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials

Oxidizing agents

7.3. Specific end uses

Recommended use

Engine oil

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Chemical Name	European Union	United Kingdom	France	Spain
Highly refined, low viscosity				VLA-EC: 10 mg/m ³
mineral oils/hydrocarbons				VLA-ED: 5 mg/m ³
(Viscosity >7 - <20.5 cSt				
@40°C)				
Highly refined base oil				VLA-EC: 10 mg/m ³
(Viscosity >20.5 cSt @40°C)				VLA-ED: 5 mg/m ³
Chemical Name	Germany	Italy	Portugal	The Netherlands
Highly refined, low viscosity		TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m³
mineral oils/hydrocarbons			STEL: 10 mg/m ³	
(Viscosity >7 - <20.5 cSt				
@40°C)				
Highly refined base oil		TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m³
(Viscosity >20.5 cSt @40°C)			STEL: 10 mg/m ³	
Chemical Name	Austria	Switzerland	Poland	Ireland
Highly refined, low viscosity			TWA: 5 mg/m ³	STEL: 10 mg/m ³
mineral oils/hydrocarbons			STEL: 10 mg/m ³	TWA: 5 mg/m ³
(Viscosity >7 - <20.5 cSt				(Mist)
@40°C)				
Highly refined base oil			TWA: 5 mg/m ³	STEL: 10 mg/m ³
(Viscosity >20.5 cSt @40°C)			STEL: 10 mg/m ³	TWA: 5 mg/m ³
				(Mist)
Chemical Name	Finland	Denmark	Norway	Sweden
Highly refined, low viscosity min		mu) TWA: 1 mg/m ³ (Olietå	åge) TWA: 1 mg/m ³ (Oljetåke)	LLV: 1 mg/m ³
oils/hydrocarbons (Viscosity >	7 -			STV: 3 mg/m ³
<20.5 cSt @40°C)				(Oljedimma)
Highly refined base oil (Viscos	ty TWA: 5mg/m ³ (Öljysu	mu) TWA: 1 mg/m ³ (Olietå	åge) TWA: 1 mg/m ³ (Oljetåke)	LLV: 1 mg/m ³
Highly refined base oil (Viscos >20.5 cSt @40°C)	ty TWA: 5mg/m ³ (Öljysu	mu) TWA: 1 mg/m ³ (Olietå	åge) TWA: 1 mg/m ³ (Oljetåke)	LLV: 1 mg/m ³ STV: 3 mg/m ³ (Oliedimma)

Chemical Name	Czech Republic	Hungary	Bulgaria	Romania
Highly refined, low viscosity	TWA: 5 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m³	TWA: 5 mg/m³
mineral oils/hydrocarbons	Ceiling: 10 mg/m ³		_	STEL: 10 mg/m ³

Revision Date: 05-16-2016

(Viscosity >7 - <20.5 cSt @40°C)				
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5 mg/m ³ Ceiling: 10 mg/m ³	TWA: 5 mg/m³	TWA: 5 mg/m³	TWA: 5 mg/m ³ STEL: 10 mg/m ³
	0	•	Tout ou	Ne stes
Chemical Name Highly refined, low viscosity	Greece TWA: 5 mg/m ³	Cyprus	Turkey	Malta
mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	°			
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5 mg/m³			
Chemical Name	Belgium	Luxembourg	Iceland	Croatia
Highly refined, low viscosity	TWA: 5 mg/m ³	Lanoning		0.000
mineral oils/hydrocarbons	STEL: 10 mg/m ³			
(Viscosity >7 - <20.5 cSt				
@40°C)				
Highly refined base oil	TWA: 5 mg/m ³			
(Viscosity >20.5 cSt @40°C)	STEL: 10 mg/m ³			
Chemical Name	Russia	Estonia	Latvia	Lithuania
Highly refined, low viscosity			TWA: 5 mg/m ³	TWA: 1 mg/m ³
mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt				STEL: 3 mg/m ³
(VISCOSILY >7 - <20.5 CSL @40°C)				
Highly refined base oil			TWA: 5 mg/m ³	TWA: 1 mg/m ³
(Viscosity >20.5 cSt @40°C)			TWA. 5 mg/m-	STEL: 3 mg/m ³
(Viscosity >20.3 cot @+0 C)				STEE. 5 Hig/III
Chemical Name	Belarus	Ukraine	Slovakia	Slovenia
Highly refined, low viscosity			TWA: 5mg/m ³	
mineral oils/hydrocarbons			-	
(Viscosity >7 - <20.5 cSt				
@40°C)				
Highly refined base oil			TWA: 5mg/m ³	
(Viscosity >20.5 cSt @40°C)			-	

Workers Systemic toxicity

Chemical Name	Long term - Oral exposure	Long term - Dermal exposure		Short term - Oral Exposure	Short term - Dermal exposure	Short term - Inhalation
			exposure			exposure
Bis(nonylphenyl)amine		0,62 mg/kg	4,37 mg/m ³			

Workers Local effects

Consumers Systemic toxicity

Chemical Name	Long term - Oral exposure	Long term - Dermal exposure		Short term - Oral Exposure	Short term - Dermal exposure	
			exposure			exposure
Bis(nonylphenyl)amine	0,31 mg/kg	0,31 mg/kg	1,09 mg/m ³			

Consumers Local effects

Predicted No Effect Concentration (PNEC)

Chemical Name	Fresh water	Sea water	Fresh water sediment	Sea sediment	Soil
Bis(nonylphenyl)amine	0.1 mg/L	0.01 mg/L	132000 mg/kg	13200 mg/kg	263000 mg/kg

8.2. Exposure controls

Engineering Measures	Ensure adequate ventilation, especially in confined areas.
Personal protective equipment Eye Protection Hand Protection	Safety glasses with side-shields. Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.
Skin and body protection Respiratory protection	Long sleeved clothing. No special protective equipment required. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Hygiene measures	Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.
Environmental Exposure Controls Thermal hazards	No special environmental precautions required. None under normal use conditions

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state @20°C Odor	liquid Hydrocarbon-like	Appearance Odor Threshold	clear amber Not Applicable
Property_ pH Melting Point / Freezing Point Boiling point/boiling range Flash point Evaporation rate Flammability (solid, gas)	<u>Values</u> No information available No information available No information available 196 °C / 385 °F No information available No information available		Note ASTM D 92
Flammability Limits in Air upper flammability limit Lower flammability limit	No information available No information available		
Vapor pressure Vapor density Relative density Solubility(ies) Partition coefficient: n-octand Autoignition temperature Decomposition temperature Viscosity, kinematic Explosive properties Oxidizing Properties	No information available No information available 0.834 Insoluble in water No Applicable No information available 48.61 cSt @ 40 °C Not Applicable Not Applicable		@15°C ASTM D 445
9.2. Other information Viscosity, kinematic (100°C) Pour point VOC Content (ASTM E-1868-1 VOC content	9.2 cSt @ 100°C -48 °C / -54 °F No information available No information available		ASTM D 445 ASTM D 97

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None under normal use conditions

10.4. Conditions to avoid

Heat, flames and sparks, Keep away from open flames, hot surfaces and sources of ignition

10.5. Incompatible Materials

Oxidizing agents

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Product Information - Principle Routes of Exposure

Inhalation	None known
Eye contact	None known
Skin contact	None known
Ingestion	None known

Acute toxicity - Product Information

Product does not present an acute toxicity hazard based on known information.

Acute toxicity - Component Information

Chemical Name	LD50 Oral (Rat)	LD50 Dermal (Rat/Rabbit)	LC50 Inhalation
Highly refined, low viscosity mineral	>2000 mg/kg	>2000 mg/kg	
oils/hydrocarbons (Viscosity >7 -			
<20.5 cSt @40°C)			
Highly refined base oil (Viscosity	>2000 mg/kg	>2000 mg/kg	
>20.5 cSt @40°C)			
Bis(nonylphenyl)amine	> 5000 mg/kg(Rat)	> 2000 mg/kg (Rat)	

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Sensitization

Revision Date: 05-16-2016

Respiratory Sensitization Skin sensitization	Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.
Germ Cell Mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
Specific target organ systemic toxicity (single exposure)	Based on available data, the classification criteria are not met
Specific target organ systemic toxicity (repeated exposure)	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

No special environmental measures are necessary

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
Bis(nonylphenyl)amine	>100: 72 h Desmodesmus subspicatus mg/L EC50	>100: 96 h Danio rerio mg/L LC50 1000: 96 h Pimephales promelas mg/L LC50 semi-static		>100: 48 h Daphnia magna mg/L EC50 14 - 28: 96 h Mysidopsis bahia mg/L LC50

12.2. Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

The product is insoluble and floats on water

12.5. Results of PBT and vPvB assessment

This preparation contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This preparation contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused Products	Dispose of in accordance with local regulations
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Observe all label precautions until container is cleaned, reconditioned or destroyed.
Other Data	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: TRANSPORT INFORMATION

14.1. UN-Number

Not regulated

14.2. UN proper shipping name

Not regulated

14.3. Transport hazard class

Not regulated

14.4. Packing group

Not regulated

14.5. Environmental Hazards

None

14.6. Special precautions for users

None

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

IMDG/IMO	Not regulated
ADR/RID	Not regulated

IATA Not regulated

ADN Not regulated

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Revision Date: 05-16-2016

The Classification, Labeling and Packaging of Substances and Mixtures (CLP) Regulation (EC 1272/2008) Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No	EC-No	REACH Registration Number
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	01-2119488706-23-xxxx
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3	01-2119487081-40-xxxx
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0	01-2119487081-40-xxxx
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6	01-2119483621-38-xxxx
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1	01-2119480374-36-xxxx
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8	01-2119489287-22-xxxx
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	01-2119480472-38-xxxx
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7	265-174-4	01-2119487080-42-xxxx
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5	01-2119485040-48-xxxx
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3	01-2119555262-43-xxxx
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9	01-2119474878-16-xxxx
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4	01-2119474889-13-xxxx
Lubricating oils	74869-22-0	278-012-2	01-2119495601-36-xxxx
White mineral oil (petroleum)	8042-47-5	232-455-8	

The highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt $@40^{\circ}$ C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No	EC-No	REACH Registration Number
Distillates (petroleum), hydrotreated heavy paraffinic	63742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	01-2119488706-23-xxxx
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3	01-2119487067-30-xxxx
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0	01-2119487081-40-xxxx
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6	01-2119483621-38-xxxx
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1	01-2119480374-36-xxxx
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8	01-2119489287-22-xxxx
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	01-2119480472-38-xxxx
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5	01-2119485040-48-xxxx
Dec-1-ene, homopolymer, hydrogenated	68037-01-4	500-183-1	01-2119486452-34-xxxx
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8	
Lubricating oils (petroleum), C20-50, hydrotreated neutral	72623-85-9	276-736-3	01-2119555262-43-xxxx

Revision Date: 05-16-2016

oil-based, high-viscosity			
Lubricating oils (petroleum), C15-30, hydrotreated neutral	72623-86-0	276-737-9	01-2119474878-16-xxxx
oil-based			
Lubricating oils (petroleum), C20-50, hydrotreated neutral	72623-87-1	276-738-4	01-2119474889-13-xxxx
oil-based			
Lubricating oils	74869-22-0	278-012-2	01-2119495601-36-xxxx

15.2. Chemical Safety Assessment

No information available

SECTION 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Repr.-Reproduction toxicity Asp. Tox. - Aspiration Toxicity Acute Tox. - Acute Toxicity Aquatic Acute - Acute Aquatic Toxicity Aquatic Chronic - Chronic Aquatic Toxicity Eye Dam. - Eye Damage Eye Irrit. - Eye Irritation Skin Corr. - Skin Corrosion Skin Irrit. - Skin Irritation Skin Sens. - Skin Sensitizer Resp. Sens. - Respiratory Sensitizer STOT SE - Specific target organ systemic toxicity (Single exposure) STOT RE - Specific target organ systemic toxicity (repeated exposure) VOC - Volatile organic compounds

Full text of H-Statements referred to under sections 2 and 3

1004 Esternalis Assessable liquid and some	11241 Supported of equains genetic defects
H224 - Extremely flammable liquid and vapor	H341 - Suspected of causing genetic defects
H225 - Highly flammable liquid and vapor	• H350 - May cause cancer
 H226 - Flammable liquid and vapor 	H351 - Suspected of causing cancer
 H270 - May cause or intensify fire; oxidizer 	 H360 - May damage fertility or the unborn child
 H271 – May cause fire or explosion; strong oxidizer 	 H361 – Suspected of damaging fertility or the unborn child
 H272 – May intensify fire; oxidizer 	 H362 - May cause harm to breast-fed children
 H290 - May be corrosive to metals 	 H370 - Causes damage to organs
• H300 - Fatal if swallowed	 H371 - May cause damage to organs
• H301 - Toxic if swallowed	 H372 - Causes damage to organs through prolonged or repeated
• H302 - Harmful if swallowed	exposure
 H304 - May be fatal if swallowed and enters airways 	 H373 – May cause damage to organs through prolonged or repeated
H310 - Fatal in contact with skin	exposure
H311 - Toxic in contact with skin	H400 - Very toxic to aquatic life
 H312 - Harmful in contact with skin 	 H410 - Very toxic to aquatic life with long lasting effects
 H314 - Causes severe skin burns and eye damage 	 H411 - Toxic to aquatic life with long lasting effects
• H315 - Causes skin irritation	H412 - Harmful to aquatic life with long lasting effects
• H317 - May cause an allergic skin reaction	H413 - May cause long lasting harmful effects to aquatic life
• H318 - Causes serious eye damage	• H360Df - May damage the unborn child. Suspected of damaging fertility
H319 - Causes serious eye irritation	H360D - May damage the unborn child
• H330 - Fatal if inhaled	H360FD - May damage fertility. May damage the unborn child
• H331 - Toxic if inhaled	• H360F - May damage fertility
• H332 - Harmful if inhaled	H361d - Suspected of damaging the unborn child
• H334 - May cause allergy or asthma symptoms or breathing difficulties	H361fd - Suspected of damaging fertility. Suspected of damaging the
if inhaled	unborn child
H335 - May cause respiratory irritation	H361f - Suspected of damaging fertility
• H336 - May cause drowsiness or dizziness	• EUH066 - Repeated exposure may cause skin dryness or cracking
• H340 - May cause genetic defects	• EUH210 - Safety data sheet available on request
	• EUH208 - May produce an allergic reaction

Exposure scenario

No information available

Revision Date:

05-16-2016

Revision Note

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.