

SAFETY DATA SHEET

Gulf HT Fluid TO-4, SAE 30

04105/30/2

Issuing Date 08-09-2017

Revision Date 08-09-2017

Version 3

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name	Gulf HT Fluid TO-4, SAE 30
Product Code(s)	04105/30/2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Automatic transmission fluids

Uses advised against Any other purpose.

1.3. Details of the supplier of the safety data sheet

Supplier

Gulf Oil Supply Company Limited B2 Industry Street, Qormi, QRM 3000, Malta +44 207 321 6219 products@gulfoilltd.com sds@gulfoilltd.com

1.4. Emergency telephone number

Europe (+) 44 808 189 0979 Code 334276 (+) 1 760 476 3961 Code 334276 (+) 32 (0) 3241 33 55

Poison Information Center (IE) +353 (0)1 809 2166 (08:00 - 22:00), (IS) +354 543 2222 telephone number

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Serious eye damage/eye irritation

Category 2 - (H319)

2.2. Label Elements



Signal word WARNING

Hazard statements

H319 - Causes serious eye irritation

Precautionary Statements - EU (§28, 1272/2008)

P280 - Wear eye protection/ face protection P264 - Wash face, hands and any exposed skin thoroughly after handling P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P337 + P313 - If eye irritation persists: Get medical advice/attention

2.3. Other hazards

No information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances / 3.2. Mixtures

This product is a mixture. Health hazard information is based on its ingredients

Chemical name	EC-No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	REACH Registration Number
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	-	50% - 100%	**	-
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	-	-	10% - 25%	Asp. Tox. 1 (H304) (EUH066)	-
Phenol, 2,2'-polythiobis[4-C8-30-alky I derivs., calcium salts, overbased	291-829-9	90480-91-4	1% - 2.5%	Aquatic Chronic 4 (H413)	01-2119524004-56-xxx x
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	272-028-3	68649-42-3	1% - 2.5%	Eye Dam. 1 (H318) Aquatic Chronic 2 (H411)	01-2119657973-23-xxx x
Aryl diesters	-	NOT AVAILABLE	1% - 2.5%	Aquatic Chronic 2 (H411)	no data available

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346. The highly refined base oil may be described by one or more of the following generic CAS identifiers: 64742-54-7, 64742-65-0, 64742-52-5, 64742-53-6, 64742-62-7, 64742-57-0, 64742-01-4, 64741-88-4, 64742-96-4, 64741-97-5, 64742-55-8, 64742-56-9, 64741-89-5, 8042-47-5. See Section 15 for additional information on base oils.

** Substances for which there are Community workplace exposure limits

Full text of H- and EUH-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice	Do not get in eyes, on skin, or on clothing. When symptoms persist or in all cases of doubt seek medical advice.
Inhalation	Move to fresh air.
Skin contact	Wash off immediately with soap and plenty of water. Remove and wash contaminated clothing before re-use.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
Ingestion	Clean mouth with water. Drink plenty of water. Do not induce vomiting without medical advice.
Protection of First-aiders	Use personal protective equipment. Avoid contact with skin, eyes and clothing.
4.2. Most important symptoms and	effects, both acute and delayed
Main Symptoms	Redness, Itching
4.3. Indication of immediate medic	al attention and special treatment needed
Notes to physician	Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment:, Use CO2, dry chemical, or foam, Water spray or fog, Cool containers / tanks with water spray

Extinguishing media which shall not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire

5.2. Special hazards arising from the substance or mixture

Special Hazard

Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). In the event of fire and/or explosion do not breathe fumes. This material creates a fire hazard because it floats on water.

Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Special protective equipment for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Advice for non-emergency Material can create slippery conditions. personnel

Advice for emergency responders For personal protection see section 8.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

6.3. Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dike to collect large liquid spills.

6.4. Reference to other sections

See Section 8/12/13 for additional information

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment. Avoid contact with skin, eyes and clothing.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials Oxidizing agent

7.3. Specific end uses

Recommended Use

Automatic transmission fluids

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

Legend

TWA - Time-Weighted Average; STEL - Short Term Exposure Limit; Ceiling - Ceiling Value

Chemical name	European Union	United Kingdom	France	Spain
Highly refined base oil				VLA-EC: 10 mg/m ³
(Viscosity >20.5 cSt @40°C)				VLA-ED: 5 mg/m ³
Highly refined, low viscosity				VLA-EC: 10 mg/m ³
mineral oils/hydrocarbons				VLA-ED: 5 mg/m ³
(Viscosity >7 - <20.5 cSt				_
@40°C)				

Spain Límites de Exposición Profesional Para Agentes Químicos en España (Ley 31/1995).

Chemical name	Germany	Italy	Portugal	Netherlands
Highly refined base oil		TWA: 5 mg/m ³	TWA: 5 mg/m ³	
(Viscosity >20.5 cSt @40°C)			STEL: 10 mg/m ³	

04105/30/2 - Gulf HT Fluid TO-4, SAE 30

Revision Date 08-09-2017

Highly refined, low viscosity	TWA: 5 mg/m ³	TWA: 5 mg/m ³	
mineral oils/hydrocarbons	_	STEL: 10 mg/m ³	
(Viscosity >7 - <20.5 cSt			
@40°C)			

Italy Istituto Superiore per la Prevenzione e la Sicurezza del Lavoro (ISPESL), Allegato XXXVIII e Allegato XLIII - Valori Limite di Esposizione Professionale.

Portugal Valores-limite e índices biológicos de exposição profissional a agentes químicos. Quadro 1 - Valores Limite de Exposição (Norma Portuguesa NP 1796:2014).

Chemical name	Austria	Switzerland	Poland	Ireland
Highly refined base oil				STEL: 10 mg/m ³
(Viscosity >20.5 cSt @40°C)				TWA: 5 mg/m³ (Mist)
Highly refined, low viscosity mineral oils/hydrocarbons				STEL: 10 mg/m ³ TWA: 5 mg/m ³
(Viscosity >7 - <20.5 cSt @40°C)				(Mist)

Ireland 2016 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001.

Chemical name	Finland	Denmark	Norway	Sweden
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5mg/m³ (Öljysumu)	TWA: 1 mg/m³ (Olietåge)	TWA: 1 mg/m³ (Oljetåke)	TWA: 1 mg/m ³ STEL: 3 mg/m ³ (Oljedimma)
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	TWA: 5mg/m³ (Öljysumu)	TWA: 1 mg/m³ (Olietåge)	TWA: 1 mg/m³ (Oljetåke)	TWA: 1 mg/m ³ STEL: 3 mg/m ³ (Oljedimma)

Finland Förordningen om koncetrationer som befunnits skadliga, 268/2014 - HTP-arvot 2014.

Denmark Bekendtgørelse om grænseværdier for stoffer og materialer. Arbejdstilsynets bekendtgørelse nr. 507 Bilag 2 Afsnit A. Norway Forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (Forskrift om tiltaks- og grenseverdier), FOR-2011-12-06-1358, FOR-2016-06-21-760, FOR-2016-12-22-1860. Sweden Arbetsmiljöverkets föreskrifter om hygieniska gränsvärden och allmänna råd om tillämpningen av föreskrifterna.

Chemical name	Czech Republic	Hungary	Bulgaria	Romania
Highly refined base oil	TWA: 5 mg/m ³		TWA: 5 mg/m ³	TWA: 5 mg/m ³
(Viscosity >20.5 cSt @40°C)	Ceiling: 10 mg/m ³			STEL: 10 mg/m ³
Highly refined, low viscosity	TWA: 5 mg/m ³		TWA: 5 mg/m ³	TWA: 5 mg/m ³
mineral oils/hydrocarbons	Ceiling: 10 mg/m ³		_	STEL: 10 mg/m ³
(Viscosity >7 - <20.5 cSt				
@40°C)				

Czech Republic Narizeni vlady 93/2012, kterym se meni narizeni vlady c.361/2007 Sb., kterym se stanovi podminky ochrany zdravi pri praci, ve zneni narizeni vlady c.68/2010 Sb.

Bulgaria НАРЕДБА #13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа.

Romania Valori Limit Obligatorii Nationale de expunere profesională ale agenților chimic - Anex Nr.1 Pubilicat în Monitorul Oficial, Partea I nr. 845.

Chemical name	Greece	Cyprus	Turkey	Malta
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5 mg/m³			
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	TWA: 5 mg/m³			

Greece Οριακές Τιμές Επαγγελματικής Έκθεσης - Προστασία της υγείας και της ασφάλειας των εργαζομένων που εκτίθενται σε ορισμένους καρκινογόνους και μεταλλαξιογόνους παράγοντες 127/2000.

Chemical name	Belgium	Luxembourg	Iceland	Croatia
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5 mg/m ³ STEL: 10 mg/m ³			
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)				

Belgium Arrêté royal relatif à la protection de la santé et de la sécurité des travailleurs contre les risques liés à des agents chimiques sur le lieu

de travail.

Chemical name	Russia	Estonia	Latvia	Lithuania
Highly refined base oil (Viscosity >20.5 cSt @40°C)			TWA: 5 mg/m ³	TWA: 1 mg/m ³ STEL: 3 mg/m ³
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)			TWA: 5 mg/m ³	TWA: 1 mg/m ³ STEL: 3 mg/m ³

Latvia Ministru Kabineta noteikumi Nr. 325 - Darba aizsardzības prasības, saskaroties ar ķīmiskajām vielām darba vietās. Lithuania Del Lietuvos higienos normos HN 23:2011 "Cheminiu medžiagu profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai".

Chemical name	Belarus	Ukraine	Slovakia	Slovenia
Highly refined base oil (Viscosity >20.5 cSt @40°C)			TWA: 5mg/m ³	
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)			TWA: 5mg/m ³	

Slovakia Nariadenie Vlády Slovenskej republiky z 16. januára 2002 o ochrane zdravia pri práci s karcinogénnymi a mutagénnymi faktormi.

Derived No Effect Level (DNEL)

Workers Systemic toxicity

Not determined

Workers Local effects

Not determined

Consumers Systemic toxicity

Not determined

Consumers Local effects

Not determined

Predicted No Effect Concentration (PNEC)

Not determined

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Showers. Eyewash stations. Ventilation systems.

Personal protective equipment

Engineering controls should be considered as the first line of protection against adverse exposure to harmful substances. Administrative controls and PPE should be used in the absence of engineering controls or as supplemental controls where engineering controls are insufficient in reducing specific exposures to an acceptable level.

Eye Protection

Safety glasses with side-shields.

Hand Protection

For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn. The following glove type may be suitable for handling this product:. Protective gloves complying with EN 374.

Glove thickness => 0.64 mm Break through time => 480 min

Glove material suitability will vary depending on specific use conditions. Consideration should be given to variables such as operational characteristics, anticipated contact time, task requirements and other factors relevant to the selection of PPE. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Any specific glove information provided is based on published literature and glove manufacturer data. Barrier creams may help to protect the exposed areas of skin. Barrier creams should not be applied after exposure has occurred. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Skin and body protection

Long sleeved clothing.

Nitrile rubber

Butvl rubber

Respiratory protection

No special protective equipment required. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

This information is based on the state in which the specific product is delivered and on the intended use specified within this SDS. This information is provided based on literature reference, manufacturer specifications and recommendations and/or derived by analogy with similar substances. The level of protection and types of exposure controls will vary depending on potential exposure conditions.

Hygiene measures

Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.

Environmental Exposure Controls

No special environmental precautions required.

Thermal hazards

None under normal use conditions

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Odor	liquid Hydrocarbon-like	Appearance Odor threshold	clear amber Not Determined
<u>Property</u> pH Melting point / freezing point Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas)	Values Not Determined Not Determined 238 °C / 460 °F Not Determined Not Determined	<u>Remarks</u> ASTM D 92	
Flammability Limit in Air Upper flammability limit: Lower flammability limit:	Not Determined Not Determined		
Vapor pressure Vapor density Relative density Solubility(ies) Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Explosive properties Oxidizing Properties	Not Determined Not Determined 0.8938 Insoluble in water Not Determined Not Determined Not Determined 86.12 cSt @ 40 °C Not applicable Not applicable	@15°C ASTM D 445	

9.2. Other information

Viscosity, kinematic (100°C)	10 cS
Pour Point	-15 °
VOC Content (ASTM E-1868-10)	Not D
VOC content	Not D

0 cSt @ 100°C 15 °C / 5 °F ot Determined ot Determined

ASTM D 445 ASTM D 97

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None under normal use conditions

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition, Extremes of temperature and direct sunlight

10.5. Incompatible materials

Oxidizing agent

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Product Information - Principle Routes of Exposure

Inhalation	None known
Eye contact	Irritating to eyes
Skin contact	None known
Ingestion	None known

Acute toxicity - Product Information

Product does not present an acute toxicity hazard based on known or supplied information.

Acute toxicity - Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 -	>2000 mg/kg	>2000 mg/kg	

<20.5 cSt @40°C)

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/eye irritation	Irritating to eyes.
Sensitization Respiratory Sensitization Skin sensitization	Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
Specific target organ systemic toxicity (single exposure)	Based on available data, the classification criteria are not met
Specific target organ systemic toxicity (repeated exposure)	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

No special environmental measures are necessary

Chemical name	Algae/aquatic plants	Fish	Crustacea
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>100: 72 h mg/L	>100: 96 h mg/L	>100: 48 h mg/L
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	>100: 72 h mg/L	>100: 96 h mg/L	>100: 48 h mg/L
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts		1.0 - 5.0: 96 h Pimephales promelas mg/L LC50 static 10.0 - 35.0: 96 h	1 - 1.5: 48 h Daphnia magna mg/L EC50
		Pimephales promelas mg/L LC50 semi-static	

12.2. Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

12.3. Bioaccumulative potential

No information available

12.4. Mobility

The product is insoluble and floats on water

12.5. Results of PBT and vPvB assessment

This preparation contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This preparation contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods	
Waste from Residues / Unused Products	Dispose of as hazardous waste in compliance with local and national regulations
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Observe all label precautions until container is cleaned, reconditioned or destroyed.
Other Data	According to the European Waste Catalog, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: TRANSPORT INFORMATION

14.1. UN-Number

Not regulated

14.2. UN proper shipping name

Not regulated

14.3. Transport hazard class

Not regulated

14.4. Packing Group

Not regulated

14.5. Environmental Hazards

None

14.6. Special precautions for users

None

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Not regulated

IATA Not regulated

ADN Not regulated

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

The Classification, Labeling and Packaging of Substances and Mixtures (CLP) Regulation (EC 1272/2008) Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006) European Agreement concerning the International Carriage of Dangerous Goods by Road Safety Data Sheet according to Regulation EC 1907/2006 (REACh) with its amendment regulation EC 2015/830 European Agreement concerning the International Carriage of Dangerous Goods by Road/ Regulations concerning the International Carriage of Dangerous Goods by Rail International Civil Aviation Organization / International Air Transport Association Dangerous Goods Regulation

Substance(s) of Very High Concern

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59).

Authorizations and/or restrictions on use:

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII). This product does not contain substances subject to authorization (Regulation (EC) No. 1907/2006 (REACH), Annex XIV).

National regulations

 Germany WGK Classification
 Hazard to water/Class 2

 Product Registration number
 4072299

 Denmark Registration (DK)
 4072299

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Chemicals Subject to Prior Informed Consent (PIC) Not applicable

International Inventories

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory All ingredients are on the inventory or exempt from listing

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List All ingredients are on the inventory or exempt from listing

AICS - Australian Inventory of Chemical Substances All ingredients are on the inventory or exempt from listing

PICCS - Philippines Inventory of Chemicals and Chemical Substances All ingredients are on the inventory or exempt from listing

KECL - Korean Existing and Evaluated Chemical Substances All ingredients are on the inventory or exempt from listing

IECSC - China Inventory of Existing Chemical Substances All ingredients are on the inventory or exempt from listing

ENCS - Japan Existing and New Chemical Substances All ingredients are on the inventory or exempt from listing

TCSI - Taiwan National Existing Chemical Inventory Contact supplier for inventory compliance status

NZIOC - New Zealand Inventory of Chemicals All ingredients are on the inventory or exempt from listing

Other Information

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical name	CAS No	EC-No	REACH Registration Number
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	01-2119488706-23-xxxx
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3	01-2119487081-40-xxxx
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0	01-2119487081-40-xxxx
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6	01-2119483621-38-xxxx
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1	01-2119480374-36-xxxx
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8	01-2119489287-22-xxxx
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	01-2119480472-38-xxxx
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7	265-174-4	01-2119487080-42-xxxx
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5	01-2119485040-48-xxxx
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3	01-2119555262-43-xxxx
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9	01-2119474878-16-xxxx
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4	01-2119474889-13-xxxx
Lubricating oils	74869-22-0	278-012-2	01-2119495601-36-xxxx
White mineral oil (petroleum)	8042-47-5	232-455-8	

The highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical name	CAS No	EC-No	REACH Registration Number
Distillates (petroleum), hydrotreated heavy paraffinic	63742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	01-2119488706-23-xxxx
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3	01-2119487067-30-xxxx
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0	01-2119487081-40-xxxx
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6	01-2119483621-38-xxxx
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1	01-2119480374-36-xxxx
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx

04105/30/2 - Gulf HT Fluid TO-4, SAE 30

Revision Date 08-09-2017

64742-53-6	265-156-6	01-2119480375-34-xxxx
64742-55-8	265-158-7	01-2119487077-29-xxxx
64742-56-9	265-159-2	01-2119480132-48-xxxx
64742-57-0	265-160-8	01-2119489287-22-xxxx
64742-58-1	265-161-3	
64742-62-7	265-166-0	01-2119480472-38-xxxx
64742-65-0	265-169-7	01-2119471299-27-xxxx
64742-71-8	265-176-5	01-2119485040-48-xxxx
68037-01-4	500-183-1	01-2119486452-34-xxxx
72623-83-7	276-735-8	
72623-85-9	276-736-3	01-2119555262-43-xxxx
72623-86-0	276-737-9	01-2119474878-16-xxxx
72623-87-1	276-738-4	01-2119474889-13-xxxx
74869-22-0	278-012-2	01-2119495601-36-xxxx
	64742-55-8 64742-56-9 64742-57-0 64742-58-1 64742-62-7 64742-65-0 64742-71-8 68037-01-4 72623-83-7 72623-83-7 72623-85-9 72623-86-0 72623-87-1	64742-55-8 265-158-7 64742-56-9 265-159-2 64742-57-0 265-160-8 64742-58-1 265-161-3 64742-62-7 265-166-0 64742-65-0 265-169-7 64742-65-0 265-169-7 64742-71-8 265-176-5 68037-01-4 500-183-1 72623-83-7 276-735-8 72623-85-9 276-736-3 72623-87-1 276-738-4

15.2. Chemical Safety Assessment

A chemical safety assessment according to regulation (EC) No. 1907/2006 is not required

SECTION 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Repr.-Reproduction toxicity Asp. Tox. - Aspiration Toxicity Acute Tox. - Acute Toxicity Aquatic Acute - Acute Aquatic Toxicity Aquatic Chronic - Chronic Aquatic Toxicity Eye Dam. - Eye Damage Eye Irrit. - Eye Irritation Skin Corr. - Skin Corrosion Skin Irrit. - Skin Irritation Skin Sens. - Skin Sensitizer Resp. Sens. - Respiratory Sensitizer STOT SE - Specific target organ systemic toxicity (Single exposure) STOT RE - Specific target organ systemic toxicity (repeated exposure) VOC - Volatile organic compounds

Full text of H-Statements which may be referred to under Sections 2 and 3

	· · · · · · · · · · · · · · · · · · ·
 H224 - Extremely flammable liquid and vapor 	 H341 - Suspected of causing genetic defects
 H225 - Highly flammable liquid and vapor 	• H350 - May cause cancer
 H226 - Flammable liquid and vapor 	 H351 - Suspected of causing cancer
 H270 - May cause or intensify fire; oxidizer 	 H360 - May damage fertility or the unborn child
 H271 - May cause fire or explosion; strong oxidizer 	 H361 - Suspected of damaging fertility or the unborn child
 H272 - May intensify fire; oxidizer 	 H362 - May cause harm to breast-fed children
H290 - May be corrosive to metals	 H370 - Causes damage to organs
H300 - Fatal if swallowed	 H371 - May cause damage to organs
H301 - Toxic if swallowed	 H372 - Causes damage to organs through prolonged or repeated
H302 - Harmful if swallowed	exposure
 H304 - May be fatal if swallowed and enters airways 	 H373 - May cause damage to organs through prolonged or repeated
H310 - Fatal in contact with skin	exposure
H311 - Toxic in contact with skin	 H400 - Very toxic to aquatic life
H312 - Harmful in contact with skin	 H410 - Very toxic to aquatic life with long lasting effects
 H314 - Causes severe skin burns and eye damage 	 H411 - Toxic to aquatic life with long lasting effects
H315 - Causes skin irritation	 H412 - Harmful to aquatic life with long lasting effects
 H317 - May cause an allergic skin reaction 	 H413 - May cause long lasting harmful effects to aquatic life
H318 - Causes serious eye damage	 H360Df - May damage the unborn child. Suspected of damaging fertility
 H319 - Causes serious eye irritation 	 H360D - May damage the unborn child
H330 - Fatal if inhaled	 H360FD - May damage fertility. May damage the unborn child
• H331 - Toxic if inhaled	 H360F - May damage fertility
H332 - Harmful if inhaled	 H361d - Suspected of damaging the unborn child
• H334 - May cause allergy or asthma symptoms or breathing difficulties	H361fd - Suspected of damaging fertility. Suspected of damaging the
if inhaled	unborn child
 H335 - May cause respiratory irritation 	 H361f - Suspected of damaging fertility
 H336 - May cause drowsiness or dizziness 	 EUH066 - Repeated exposure may cause skin dryness or cracking
H340 - May cause genetic defects	 EUH210 - Safety data sheet available on request
	 EUH208 - May produce an allergic reaction

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]

Physical hazards Health Hazards Environmental Hazards	On basis of test data Calculation Method Calculation Method
Revision Date	08-09-2017
Revision Note	This SDS has been revised in the following section(s), 3, 8, 15, 16.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.