

Coastal® TC-W3 2-Cycle Engine Oil

Coastal TC-W3 2-Cycle Engine Oil is formulated with highly refined base stocks, along with ashless additives to provide outstanding protection against piston scuffing, bearing wear, ring sticking and rust in marine applications where a certified National Marine Manufacturer's Association (NMMA) TC-W3[®] lubricant is required.

Coastal TC-W3 2-Cycle Engine Oil is also recommended for use in applications where TC-W[®], TC-WII[®], TC-W3[®] and the JASO FB and JASO FC two-cycle air-cooled category's are required.

Coastal TC-W3 2-Cycle Engine Oil exceeds the warranty requirements of Evinrude[®], Mercury[®], Johnson[®], Yamaha[®], Mariner[®], Suzuki[®] as well as all other makes and models of High Performance Outboard Engines and all two-cycle engines. It may also be used in both oil-injected engines as well as those where the oil is mixed with the fuel.

Coastal TC-W3 2-Cycle Engine Oil is dyed BLUE for easy identification.

Benefits

- Resistant to piston scuffing and ring sticking
- Minimizes engine deposits and port plugging
- Mixes readily with gasoline
- Dyed for easy identification
- Provides rust and corrosion protection



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210: Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



Coastal® TC-W3 2-Cycle Engine Oil

Fuel Mixing Table

Ounces of Oil to Gallon of Gasoline (U.S. Measure)

| Ratio Gas to Oil | 1 Gal. oz. | 2 Gal. oz. | 3 Gal. oz. | 4 Gal. oz. | 5 Gal. oz. | 6 Gal. oz. |
|------------------------|---------------|---------------|---------------|---------------|---------------|---------------|
| 16:1 | 8 | 16 | 24 | 32 | 40 | 48 |
| 20:1 | 6 | 13 | 19 | 26 | 32 | 38 |
| 25:1 | 5 | 10 | 15 | 20 | 26 | 31 |
| 50:1 | 3 | 5 | 8 | 10 | 13 | 16 |
| 100:1 | 1.5 | 2.6 | 4 | 5 | 6.4 | 8 |

Typical Characteristics

| Viscosity | | | |
|--------------------------|-----------|--|--|
| @40 °C, cSt | 45.0 | | |
| @100 °C, cSt | 7.94 | | |
| Viscosity Index | 149 | | |
| Color | Blue | | |
| Pour Point °F | -40°F | | |
| API Gravity | 32.0 | | |
| Ash, wt % | 0 | | |
| NMMA Registration Number | RL-70172F | | |

