



LubriGold[®] Full Synthetic CVT Fluid

LubriGold Full Synthetic CVT Fluid is a multi-vehicle continuously variable transmission fluid suitable for use in most belt or chain CVT applications. Formulated with synthetic base stocks to insure long life and compounded with an additive package to insure exceptional metal-to-metal frictional properties and provide outstanding anti-shudder durability. The extremely low pour point will provide protection during cold weather start-up.

LubriGold Full Synthetic CVT Fluid provides a well-balanced, high level of both torque capacity and anti-shudder performance to provide enhanced driver comfort and long transmission life. NOTE: Not for use in hybrid CVT units such as those in the Toyota Prius or Ford Escape.

Benefits

- Full synthetic long life formula
- Outstanding metal-to-metal friction performance
- Excellent wear resistance
- Excellent low temperature fluidity
- Outstanding anti-shudder durability



Warren Oil Company, Inc

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



LubriGold[®] Full Synthetic CVT Fluid

Recommended for the following CVT applications:

Audi CVT G052 180 A2 (TL52180)	Mini Cooper EZL799
BMW EZL 799	Mitsubishi CVTF-J1
Daihatsu AMMIX CVT, TC	Mitsubishi CVTF-J4
Dodge/Jeep/Chrysler NS-2	Mitsubishi SP-III (CVT)
Dodge/Chrysler/Jeep CVT+4	Nissan CVT NS-1, -2, -3
Ford CFT or CVT 23	Subaru DEX CVT (VTF)
Ford/Mercury <3.5L engine XT-7-QCFT (VFT/CVT)	Subaru iCVT
GM/Saturn DEX-CVT	Subaru CVT SOA868V9245QT
Honda CVT Fluid	Subaru iCVT FG
Honda HMMF (without starting clutch)	Subaru ECVT
Honda HCF2	Subaru Chain CVT Lineartronics
Honda Z-1 (CVT model)	Suzuki CVTF TC
Hyundai/Kia CVT-J1, SP III (CVT)	Suzuki CVTF 3320
JASO M315-2013 1A	Suzuki NS-2
JASO M315-2013 1A-LV	Suzuki CVT Green 1 & 2
JASO M315-2013 2A	Toyota CVTF TC
Mazda JWS 3320, TC	Toyota CVTF FE
MB 236.20	VW CVT (TL 52180, G 052 180 A2)

NOTE: Not for use in hybrid CVT units such as those in the Toyota Prius or Ford Escape.



Warren Oil Company, Inc

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301



LubriGold[®] Full Synthetic CVT Fluid

Typical Characteristics:

API Gravity @ 60°F	35.1
Sp. Gr. @ 60°F	0.849
Flash, COC, °F	428
Color	Red
Pour Pt., °F	-60
Viscosity,	
cSt @ 40°C	35.9
cSt @ 100°C	7.3
Viscosity Index	174
Brookfield Vis @ -40°C, cP	13,780
Part Number	
6/1 QT	402292



Warren Oil Company, Inc

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301