

Coastal® Multitrac Tractor Fluid

COASTAL MULTITRAC TRACTOR FLUID is a high quality, specially designed lubricant containing anti-rust, anti-foam and oxidation inhibitors; plus other additives necessary for the wide range of applications recommended by various tractor manufacturers. The product is an "all-season" type of oil that resists thickening in cold weather and thinning in the heat of the summer. It is compounded with detergents to keep transmissions clean and maintain hydraulic control circuits in perfect working condition; and provides excellent protection against seal and pump deterioration. Operators, especially farmers, will appreciate the multipurpose application of COASTAL MULTITRAC TRACTOR FLUID for transmissions, final drives, and hydraulic systems of tractors.

COASTAL MULTITRAC TRACTOR FLUID is currently being used in a variety of mechanical systems world-wide.

Benefits

- Excellent gear, bearing and pump wear protection
- Multi-functional fluid
- Oxidation and thermal stability for long life
- Excellent rust and corrosion protection
- Reduces brake chatter
- Compatibility with oil seal materials used in transmission and hydraulic systems



Warren Oil Company, LLC



Coastal® Multitrac Tractor Fluid

COASTAL MULTITRAC TRACTOR FLUID may be used in transmissions and hydraulic systems of equipment made by:

AGCO (Deutz-Allis): Power Fluid 821XL

Allison: Type C-3

Allis-Chalmers: #272843

Caterpillar: TO-2

Denison: HF-0, HF-1, HF-2

Ford New Holland: M-2C134-A/B/C/D, M-2C48-B, M-2C53-B, M-2C86-A&C,

ESN-M2C41-B, FNHA-2-C-200 & 201, MAT 3525, NH Multi-G 134

International Harvester: Hy-Tran[®] (B-6)

J.I. Case: JIC 143, JIC 144, JIC 145, JIC 185, MS-1209, MS-1207, MS-1206, MS-1204

MS-1210 (TCH Fluid)

John Deere: J20C, Quatrol[®], J20A, J14B, J14C, J21A

Kubota: UDT Fluid, Super UDT Fluid

Massey Ferguson: M-1110, M-1127A/B, M-1129, M-1135 (Permatran[®] III),

M-1138, M-1141, M-1145

Oliver: Type 55 Steiger: SEMS 17001 Sundstrand Hydraulics Versatile: 23M or 24M

Vickers: M-92950-S, I-286-S, 35VQ25

White: Q1722, Q1826

The above trademarks are the property of their respective trademark holders.

Please consult manufacturer's specifications for proper application.



Warren Oil Company, LLC



Coastal® Multitrac Tractor Fluid

Typical Characteristics:

COASTAL MULTITRAC TRACTOR FLUID	
SAE Grade	10W-30
SAE Grade, Gear	80
API Gear Performance	GL-4
Viscosity	
@ 40 Deg. °C, cSt	59
@100 Deg. °C, cSt	9.4
@100 Deg. °F, SUS	274
@210 Deg. °F, SUS	57.2
Viscosity Index	140
Flash Point, Deg. °F	400
Pour Point, Deg. °F	-40
Gravity, Deg API @ 60 °F	30.8
Density, lb/gal	7.24



Warren Oil Company, LLC