

MATERIAL SAFETY DATA SHEET**Warren Unilube, Inc.**

Address: 915 E. Jefferson Ave.
West Memphis, AR 72301

Phone: (800) 428-9284

Chemtrec Number:
Domestic: (800) 424-9300
International: (703) 527-3887

SECTION 1: PRODUCT IDENTIFICATION

Trade Name: AUTOGUARD Premium Multi-Purpose Lithium EP Grease
Date Revised: March 12, 2012
Synonyms/Product Code: Lubricating Grease
Chemical Name: Petroleum Hydrocarbons
Family Description: A complex combination of petroleum hydrocarbons containing soap and additives.
DOT Hazard Class: Not Available

NFPA Codes: Health=1, Flammability=1, Reactivity=0

SECTION 2: COMPOSITION

COMPONENT NAME(S)	CAS REGISTRY NO.	CONCENTRATION (%)
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4	30 – 50
Distillates, petroleum, hydrotreated heavy naphthenic	64742-52-5	20 – 40
Residual oils, petroleum, solvent-refined	64742-01-4	10 – 30
Lithium carboxylate	Property Mixture	1 – 15
Proprietary Ingredients	Property Mixture	<2
Phosphorodithioic acid O, O-di-C1-14-alkyl Esters, zinc salts	68649-42-3	<1

SECTION 3: HEALTH HAZARD DATA

Major Route(s) of Entry: Skin contact

Signs and Symptoms of Acute Exposure:

Inhalation: No significant adverse health effects are expected to occur upon short-term exposure at ambient temperatures. At elevated temperatures, product vapor may cause respiratory tract irritation. Repeated or prolonged over-exposure to product mists can result in respiratory tract inflammation and an increased risk of infection.

Eye Contact: This product can cause transient mild eye irritation with short-term contact with liquid sprays or mists. Symptoms include stinging, watering, redness, and swelling.

Skin Contact: This material can cause mild skin irritation from prolonged or repeated skin contact. Injection under the skin can cause inflammation and swelling. Injection of pressurized hydrocarbons can cause severe, permanent tissue damage. Initial symptoms may be minor. Injection of petroleum hydrocarbons requires immediate medical attention. Skin contact with hot material may result in severe burns.

Ingestion: This material can cause a laxative effect. If swallowed in large quantities, this material can obstruct the intestine.

Chronic Health Effects Summary: This product contains a petroleum-based mineral oil. Prolonged or repeated skin contact can cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil acne. Repeated or prolonged inhalation of petroleum-based mineral oils mists at concentrations above applicable workplace exposure levels can cause respiratory irritation or other pulmonary effects.

Conditions Aggravated by Exposure: Disorders of the following organs or organ systems that may be aggravated by significant exposure to this material or its components include: Skin

Target Organs: May cause damage to the following: Skin

Carcinogenic Potential: This product is not known to contain any components at concentrations above 0.1% which are considered carcinogenic by OSHA, IARC or NTP.

OSHA Hazard Classification is indicated by an "X" adjacent to the hazard title. If no "X" is present, the product does not exhibit the hazard as defined in the OSHA Hazard Communication Standard (29 CFR 1910.1200).				
OSHA Health Hazard Classification		OSHA Physical Hazard Classification		
Irritant	Sensitizer	Combustible	Explosive	Pyrophoric
Toxic	Highly Toxic	Flammable	Oxidizer	Water-reactive
Corrosive	Carcinogenic	Compressed Gas	Organic Peroxide	Unstable

SECTION 4: FIRST AID MEASURES

Inhalation: Vaporization is not expected at ambient temperatures. This material is not expected to cause inhalation-related disorders under anticipated conditions of use. In case of overexposure, move the person to fresh air.

Eye Contact: Check for and remove contact lenses. Flush eyes with cool, clean, low-pressure water while occasionally lifting and lowering eyelids. Seek medical attention if excessive tearing, redness, or pain persists.

Skin Contact: If burned by hot material, cool skin by quenching with large amounts of cool water. For contact with product at ambient temperatures, remove contaminated shoes and clothing. Wipe off excess material. Wash exposed skin with mild soap and water. Seek medical attention if tissue appears damaged or if pain or irritation persists. Thoroughly clean contaminated clothing before reuse. Clean or discard contaminated leather goods. If material is injected under the skin, seek medical attention immediately.

Ingestion: Do not induce vomiting unless directed to by a physician. Rinse out mouth with water. Never give anything by mouth to a person who is not fully conscious. Allow small quantities to pass through the digestive system. If large amounts are swallowed or irritation or discomfort occurs, seek medical attention immediately.

NOTES TO PHYSICIAN:

Skin: In the event of injection in underlying tissue, immediate treatment should include extensive incision, debridement and saline irrigation. Inadequate treatment can result in ischemia and gangrene. Early symptoms may be minimal.

Ingestion: Check for possible bowel obstruction with ingestion of large quantities of material.

SECTION 5: FIRE FIGHTING MEASURES

Flash Point:	Open cup: 238°C (460°F) (Cleveland)
NFPA Flammability Classification:	NFPA Class-IIIB combustible material
Lower Flammable Limit:	N.A. Upper: N.A.
Autoignition Temperature:	N.A.

Hazardous Combustion Products: Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and trace oxides of sulfur, antimony, phosphorus and/or nitrogen.

Special Properties: Fight the fire from a safe distance in a protected location. Open any masses with a water stream to prevent reignition due to smoldering. Cool surface with water fog. Molten material can form flaming droplets if ignited. Water or foam can cause frothing. Use of water on product above 100°C (212°F) can cause product to expand with explosive force. Do not allow liquid runoff to enter sewers or public waters.

Extinguishing Media: Use dry chemical, foam, carbon dioxide or water fog. Water or foam may cause frothing. Carbon dioxide and inert gas can displace oxygen. Use caution when applying carbon dioxide or inert gas in confined spaces.

Protection of Fire Fighters: Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Take proper precautions to ensure your own health and safety before attempting spill control or clean-up. For more specific information, refer to the Emergency Overview on Page 1, Exposure Controls and Personal Protection in Section 8 and Disposal Considerations in Section 13 of this MSDS.

Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Slipping hazard; do not walk through spilled material. Stop leak if you can do so without risk. For small spills, absorb or cover with dry earth, sand, or other inert non-combustible absorbent material and place into waste containers for later disposal. Contain large spills to maximize product recovery or disposal. Prevent entry into the waterways or sewers. In urban area, clean up spill as soon as possible. In natural environments, seek cleanup advice from specialists to minimize physical habitat damage. This material will float on water. Absorbent pads and similar materials can be used. Comply with all laws and regulations.

SECTION 7: HANDLING AND STORAGE

Handling: If this product is stored or applied in high-pressure systems such as grease guns or hydraulic lines, there is the potential for accidental injection into the skin and underlying tissues. Hydrocarbons injected into the skin or underlying tissues are not readily removed by body fluids and can cause pain, swelling, chemical irritation, infection and tissue destruction. Early symptoms may be minimal. Workers must be aware of the significant hazards associated with a hydrocarbon injection injury. In the event of an injection injury, workers should seek medical treatment immediately. Avoid water contamination and elevated temperatures to minimize product degradation. Empty containers may contain product residues that can ignite with explosive force. Do not pressurize, cut, weld, braze solder, drill, grind or expose containers to flames, sparks, heat or other potential ignition sources. Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers and/or waste residues of this product.

Storage: Keep container tightly closed. Store in a cool, dry, well-ventilated area. Store only in approved containers. Do not store with strong oxidizing agents. Do not store with strong oxidizing agents. Do not store at elevated temperatures. Avoid storing product in direct sunlight for extended periods of time. Storage area must meet OSHA requirements and applicable fire codes. Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers or waste residues of this product.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls: Ventilation controls are not normally required under anticipated conditions of use. Provide exhaust ventilation or other engineering controls if airborne mists or vapors concentrations exceed recommended occupational exposure limits listed below. An eye wash station and safety shower should be located near the workstation.

Personal Protective Equipment: Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a

qualified professional pursuant to OSHA regulations. The following pictograms represent the minimum requirements for personal protective equipment. For certain operations, additional PPE may be required.



Eye Protection: Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. Wear goggles if splashing or spraying is anticipated. Wear goggles and face shield if material is heated above 125°F (51°C). Have suitable eye wash water available.

Hand Protection: None required for incidental contact. Use gloves constructed of chemical resistant materials such as heavy nitrile rubber if frequent or prolonged contact is expected. Use heat-protective gloves when handling product at elevated temperatures.

Body Protection: Use clean protective clothing if splashing or spraying conditions are present. Protective clothing may include long-sleeve outer garment, apron, or lab coat. If significant contact occurs, remove oil-contaminated clothing as soon as possible and promptly shower. Launder contaminated clothing before reuse or discard. Wear heat protective boots and protective clothing when handling material at elevated temperatures.

Respiratory Protection: The need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist pre-filter should be used. Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134).

General Comments: Use good personal hygiene practices. Wash hands and other exposed skin areas with plenty of mild soap and water before eating, drinking, smoking, use of toilet facilities, or leaving work. DO NOT use gasoline, kerosene, solvents or harsh abrasives as skin cleaners. Since specific exposure standards/control limits have not been established for this product, the “Oil Mist, Mineral” exposure limits shown below are suggested as minimum control guidelines.

OCCUPATIONAL EXPOSURE GUIDELINES

Substance:	Applicable Workplace Exposure Levels
Oil Mist, Mineral	ACGIH (United States) TWA: 5 mg/m ³ STEL: 10 mg/m ³ OSHA (United States) TWA: 5 mg/m ³
Antimony and Antimony Compounds	ACGIH (United States) TWA: 5 mg/m ³ TWA: 5 mg/m ³

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Semi-solid to solid	Color: Dark amber to black	Odor: Petroleum
Specific Gravity:	<1 (Water = 1)	pH: N.A.	Vapor Density: >10 (Air =1)
Boiling Range:	N.A.	Melting/Freezing Point:	N.A.
Vapor Pressure:	<0.001 kPa (,0.01 mm Hg)(at 20°C)		Volatility: Negligible volatility

Solubility in H₂O:	Negligible solubility in cold water	Viscosity: N.A. (cSt @ 40°C)
Flash Point:	Open cup: 238°C (460°F)(Cleveland)	
Additional Properties:	NLGI Grade = 2 Thickener = Lithium Texture = Smooth	

N.A. = Not Available

SECTION 10: STABILITY AND REACTIVITY DATA

Chemical Stability:	Stable	Hazardous Polymerization: Not expected to occur
Conditions to Avoid:	Keep away from extreme heat, sparks, open flame, and strongly oxidizing conditions.	
Materials Incompatibility:	Strong oxidizers	
Hazardous Decomposition Products:	No additional hazardous decomposition products were identified other than the combustion products identified in Section 5 of this MSDS.	

SECTION 11: TOXICOLOGICAL INFORMATION

For other health-related information, refer to the Emergency Overview on Page 1 and the Hazards Identification in Section 3 of this MSDS.

Toxicity Data:	Highly-refined petroleum lubricant oils	
	ORAL (LD50):	Acute: >5000 mg/kg [Rat]
	DERMAL (LD50):	Acute: .2000 mg/kg [Rabbit]

Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipid granuloma formation and lipid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place exposure levels produced no significant toxicological effects. In long term studies (up to two years) no carcinogenic effects have been reported in any animal species tested.

Asphalt	ORAL (LD50):	Acute: >5000 mg/kg [Rat]
	DERMAL (LD50):	Acute: >2000 mg/kg [Rabbit]

Asphalt fumes have been associated with eye, skin and respiratory tract irritation. Repeated or prolonged contact with asphalt at ambient temperatures can result in skin irritation. Long-term exposure can cause dermatitis, acne, photosensitization and, more rarely, pigmentation of the skin. The International Agency for Research on Cancer (IARC) has determined that there is sufficient evidence for the carcinogenicity of extracts of steam-refined bitumens, air refined bitumens and pooled mixtures of steam- and air-refined bitumens in experimental animals. Further, IARC has determined that there is limited evidence for the carcinogenicity of undiluted steam-refined bitumens in experimental animals. Also, IARC determined that there is inadequate evidence that bitumens alone are carcinogenic to humans.

Grease: Injection of pressurized hydrocarbons under the skin, in muscle or into the blood stream can cause irritation, inflammation, swelling, fever and mild central nervous system depression. Injection of pressurized hydrocarbons can cause severe, permanent tissue damage.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: Ecotoxicity data are not available for this product.

Environmental Fate: An environmental fate analysis is not available for this specific product. Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterways may be sufficient to cause a fish kill or create an anaerobic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

Conditions of use may cause this material to become a “hazardous waste” as defined by federal or state regulations. It is the responsibility of the user to determine if the material is a “hazardous waste” at the time of disposal. Transportation, treatment, storage, and disposal of waste material must be conducted in accordance with RCRA regulations (see 40 CFR 260 through 40 CFR 271). State and/or local regulations may be more effective. Contact your regional US EPA office for guidance concerning case specific disposal issues. Empty drums and pails retain residue. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose this product’s empty container to heat, flame, or other ignition sources. DO NOT attempt to clean it. Empty drums and pails should be drained completely, properly bunged or sealed, and promptly sent to a reconditioner.

SECTION 14: TRANSPORT INFORMATION

The shipping description below may not represent requirements for all modes of transportation, shipping methods or locations outside of the United States.

US DOT Status:	Not regulated by the U.S. Department of Transportation as a hazardous material.		
Proper Shipping Name:	Not regulated.		
Hazard Class:	Not regulated.	Packing Group:	Not applicable
		UN/NA Number:	Not regulated
Reportable Quantity:	A Reportable Quantity (RQ) has not been established for this material.		
Placard(s)	Emergency Response Guide No.:	Not applicable	
	MARPOL III STATUS:	Not a DOT “Marine Pollutant” per 49 CFR 171.8	

Oil: The product(s) represented by this MSDS is (are) regulated as “oil” under 49 CFR Part 130. Shipments by rail or highway in packaging having a capacity of 3500 gallons or more or in a quantity greater 42,000 gallons are subject to these requirements. In addition, mixtures containing 10% or more of this product may be subject to these requirements.

SECTION 15: REGULATORY INFORMATION

TSCA Inventory: This product and/or its components are listed on the Toxic Substance Control Act (TSCA) inventory.

SARA 302/304 Emergency Planning and Notification: The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to Subparts 302 and 304 to submit emergency planning and notification information based on Threshold Planning Quantities (TPQs) and Reportable Quantities (RQs) for “Extremely Hazardous Substances” listed in 40 CFR 302.4 and 40 CFR 355. No components were identified.

SARA 311/312 Hazard Identification: The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to this subpart to submit aggregate information on chemicals by “Hazard Category” as defined in 40 CFR 370.2. This material would be classified under the following hazard categories:

No SARA 311/312 hazard categories identified.

SARA 313 Toxic Chemical Notification and Release Reporting: This product contains the following components in concentrations above *de minimis* levels that are listed as toxic chemicals in 40 CFR Part 372 pursuant to the requirements of Section 313 of SARA: No components were identified.

CERCLA: The Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Requires notification of the National Response Center concerning release of quantities of “hazardous substances” equal to or greater than the reportable quantities (RQ’s) listed in 40 CFR 302.4. As defined by CERCLA, the term “hazardous substance” does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically designated in 40 CFR 302.4. Chemical substances present in this product or refinery stream that may be subject to this statute are:

Zinc and Zinc Compounds, Concentration: <1%

Clean Water Act (CWA): This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA’s National Response Center at (800) 424-8802.

California Proposition 65: This material may contain the following components which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5): Toluene: <0.001%

New Jersey Right-to-Know Label: Petroleum Oil

Additional Remarks: No additional regulatory remarks.

SECTION 16: OTHER INFORMATION

Refer to the top of Page 1 for the HMIS and NFPA Hazard Ratings for this product.

ABBREVIATIONS

AP: Approximately	EQ: Equal	>: Greater Than	<: Less Than
NA: Not Applicable	ND: No Data	NE: Not Established	
ACGIH:	American Conference of Governmental Industrial Hygienists		
AIHA:	American Industrial Hygiene Association		
IARC:	International Agency for Research on Cancer		
NIOSH:	National Institute of Occupational Safety and Health		
NPCA:	National Paint and Coating Manufacturers Association		
EPA:	US Environmental Protection Agency		
HMIS:	Hazardous Materials Information System		
OSHA:	Occupational Safety and Health Administration		
NTP:	National Toxicology Program		
NFPA:	National Fire Protection Association		

DISCLAIMER OF LIABILITY

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THIS COMPANY'S KNOWLEDGE AND BELIEVED ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO THE ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABLENESS AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE.