



Lubriguard™ GL-5 Gear Lubricant

Lubriguard GL-5 Gear Lubricants are multi-purpose sulfur/phosphorous gear lubricants designed for API Service Classification “GL-5” and “MT-1”.

Lubriguard GL-5 Gear Lubricants are compounded with highly refined base stocks and additives to ensure extreme pressure characteristics, anti-wear, corrosion inhibition, rust prevention, low pour point, and anti-foaming performance. It is fully formulated for limited slip differentials.

Lubriguard GL-5 Gear Lubricants meet the requirements of U.S. Military Specification MIL-L-2105D, MIL-L-2105E, SAE J2360, and Mack GO-J.

Lubriguard GL-5 Gear Lubricants are recommended for use in limited slip and conventional differentials of cars, pick up trucks, sport utility vehicles, and heavy duty trucks. Always check owner’s manual for proper recommendation.

Benefits

- Excellent wear protection
- Shear resistant
- Excellent rust and corrosion protection
- Excellent Demulsibility, separates water readily
- Full Limited Slip performance



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



Lubriguard™ GL-5 Gear Lubricant

Typical Characteristics

Lubriguard GL-5 Gear Lubricant			
SAE Viscosity Grade		80W-90	85W-140
Pour Point Deg F.		-15	+5
Flash Point, COC, °F		420	430
Viscosity			
@ 40°C, cSt		140	345
@100°C, cSt		14.6	26.3
Viscosity Index		95	95
Gravity, API		24.5	24.6
Color		2.5	3.0
Rust Test, ASTM D665		Pass	Pass
Product Code #			
Bulk		13100	13200
Drum		702606	702603
Keg		702841	702595
Pail		702629	702575
Case 6/1 Gallon		702753	702563
Case 12/1 Quart		702630	702628



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
 Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301