



LubriGuard™ Heavy Duty SAE 25W-60 Diesel Engine Oil

LUBRIGUARD HEAVY DUTY SAE 25W-60 DIESEL ENGINE OIL is specially formulated for diesel engines operating in severe conditions where additional viscosity protection is required.

LUBRIGUARD HEAVY DUTY SAE 25W-60 DIESEL ENGINE OIL combines high quality base oils with high performance additives to provide superb performance in the areas of detergency and dispersancy and protection against wear, rust, corrosion and high temperature thickening. It meets or exceeds the requirements for API CF.

Benefits

- Resists breakdown under high temperatures
- Maintains oil pressure under heavy load conditions
- Outstanding rust and corrosion protection
- Excellent wear protection

CAUTION: THIS OIL IS RATED API PERFORMANCE CATEGORY CF. IT IS NOT SUITABLE FOR USE IN MOST DIESEL POWERED AUTOMOTIVE ENGINES BUILT AFTER 2009. LATER "C" CATEGORY OILS ARE USUALLY SUITABLE OR PREFERRED FOR DIESEL AUTOMOTIVE ENGINE FOR WHICH "CF" OILS WERE SPECIFIED. OLDER EQUIPMENT AND/OR TWO-STROKE DIESEL ENGINES, ESPECIALLY THOSE CALLING FOR MONOGRADE PRODUCTS, MAY HOWEVER REQUIRE "CF" CATEGORY OIL. CONSULT WITH YOUR ENGINE MANUFACTURER TO ENSURE YOUR EQUIPMENT IS STILL BEST SERVED BY CF CATEGORY PRODUCTS.



Warren Oil Company, LLC

*Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301*



LubriGuard™ Heavy Duty SAE 25W-60 Diesel Engine Oil

Typical Characteristics:

API Gravity @ 60°F	29.0
Specific Gravity @ 60°F	0.882
Flash Pt., COC, °F	420
Pour Pt., °C	-25
Viscosity,	
cSt @ 40°C	217
cSt @ 100°C	23.9
Viscosity Index	137
Sulfated Ash, wt%	0.7
Zinc, wt%	0.089
TBN, ASTM D2896	7



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301