



## Autoguard<sup>®</sup> Premium Moly EP Grease

---

**AUTOGUARD PREMIUM MOLY EP GREASE** is recommended for use where NLGI No. 2 EP multipurpose grease is specified. Applications include all types of heavy duty equipment operating under adverse conditions: industrial, off-highway, mining, construction, trucking and farming applications. It can be used in journal and anti-friction bearings, electric motors, gear coupling, automotive chassis, wheel bearings (except high temperature applications) and universal joints, as well as many other industrial applications. It is not recommended for disc brake wheel bearings.

**AUTOGUARD PREMIUM MOLY EP GREASE** is an NLGI No. 2 grease containing molybdenum disulfide for protection against wear, and graphite to reduce friction.

**AUTOGUARD PREMIUM MOLY EP GREASE** is highly resistant to water washout, gives excellent performance in the areas of oxidation stability and corrosion protection, and resists leakage, dripping or undesirable throw-off from the lubricated surface.

**AUTOGUARD PREMIUM MOLY EP GREASE** meets the performance requirements of Ford ESA-M1C75B and Mack Multi-Purpose MG-C.

### Benefits

- Highly resistant to water washout
- Contains molybdenum disulfide for added protection against wear
- Contains graphite to reduce friction
- Meets requirements of NLGI Service Classification LB



**Warren Oil Company, Inc**

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;  
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301



## Autoguard<sup>®</sup> Premium Moly EP Grease

### Typical Specifications:

NLGI NO.	2
Appearance	Bluish/Gray/Black
Texture	Smooth, Adhesive
Thickener	Lithium 12-Hydroxystearate
Fillers	
Molybdenum Disulfide, % wt.	1.0
Worked Penetration, ASTM D-217 @ 72°F	265-295
Dropping Pt., ASTM D-566, °F	350
Base Oil Viscosity	
cSt @ 40°C	187
cSt @ 100°C	15.8
SUS @ 100°F	987
SUS @ 210°F	83
Timken OK Load, ASTM D-2509, lbs.	45 Min.
Four-Ball EPWeld Point, ASTM D-2596, kgf	200 Min.
Operating Range, Continuous, °F	0 to 290



**Warren Oil Company, Inc**

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;  
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301